

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-23 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions

# Please read BOTH these Installation Instructions and the General Information sheet prior to installing or operating this equipment.

**Serial Number** 

Attachment Tab Height: 28"

Attachment Tab Width: 31"







If the front of your vehicle looks different than this, please contact us at (402)385-3051.

- Blue Ox® towing products and accessories are intended to be installed by Blue Ox® Dealers who are familiar with our products and have the equipment and knowledge necessary to do "fit work". If needed, Blue Ox® Dealers can be found at www.blueox.com or by contacting our Technical Service Department at (402) 385-3051.
- 2. Many Blue Ox® baseplates are designed to use existing holes and hardware to mount the baseplate to the towed vehicle. Even though bolts are there, do not assume they are adequate for baseplate mounting. Always use the hardware supplied in the hardware kit and existing hardware as specified in the installation instructions.

### **Bolt Torque Specifications**Torque in Foot-Pounds for Inch Bolts

<b>Bolt Size</b>	Grade 5	Grade 8	
1/4"	10	14	
5/16"	19	29	
3/8"	33	47	
7/16"	54	78	
1/2"	78	119	
5/8"	154	230	
3/4"	257	380	

### **Bolt Torque Specifications**Torque in Foot-Pounds for Metric Bolts

<b>Bolt Size</b>	Grade 8.8	Grade 10.9	
6MM	6	8	
8MM	16	22	
10MM	31	40	
12MM	54	70	
14MM	89	117	
16MM	161	230	
18MM	222	318	

## **MARNING**

Failure to read and follow these instructions could result in separation of the towed vehicle from the tow bar, causing property damage, loss of towed vehicle, personal injury or death.

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions

#### Reference your vehicle owner's manual for manufacturer's towing specifications.

**Instruction Notes:** The fascia and windshield washer fluid reservoir are removed and reinstalled for the baseplate installation. Some drilling and trimming is required.

Place all components that are removed on a flat, sturdy surface. All items will be reinstalled unless otherwise noted after the baseplate is installed.


The dimensional variations between otherwise identical vehicles can be considerable. While the baseplate was designed for easy installation, it may be necessary to tailor the baseplate slightly to compensate for vehicle manufacturer's tolerances.

The BX8848 Tail Light Wiring Kit is recommended for this vehicle.

#### Tail Light Housing Removal Instructions



1. Using a Phillip's screw driver, remove the three (3) push pins. Unsnap black plastic piece. Do this on both sides of the vehicle.




2. Unsnap fascia trim piece between tail light and black plastic at the bottom. Do this on both sides of the vehicle.

continued on page 3

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions



 Carefully unsnap and remove plastic piece below tail light. Do this on both sides of the vehicle.




4. Using an 8MM socket, remove the two (2) bolts (white) and using a 10MM socket remove the two (2) bolts (gray, insets) attaching the tail light housing to the frame. Remove the tail light housing and install tail light wiring kit per kit instructions. Do this on both sides of the vehicle.

5. Once wiring kit has been installed, reinstall tail light housing.

#### **NOTICE**

- Handling of some cosmetic parts when installing this product may require the use of protective covers, rags, specialty tools, etc. to prevent damage.
- When using power drills be aware of the dangers of torque and drill bit length.
- When using a reciprocating saw be aware of objects behind the cutting surface.
- Use a good quality paint to spray cut edges of frame to prevent rusting.
- Be sure that **ALL** electrical connections are plugged in and accessories are functioning properly before reinstalling the fascia.
- The baseplate is computer tested to your vehicle's GVWR, exceeding this weight will void the manufacturer's warranty.
- Be sure to use a sufficient amount of Loctite® Red on all bolt threads before tightening. Tighten all bolts according to the torque chart provided unless specified.
- Dealer or installer be certain the user receives these instruction sheets.
- If the baseplate is in an accident, it must be replaced. DO NOT use it again! An accident can cause
  unseen damage and using it again could result in more damage or serious injury. DO NOT use the
  baseplate if it is damaged or missing parts.

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions




Item No.	Part No.	Description	Qty.
		M12 x 1.75MM Bolt	6
2	61-8611	BX2692 Baseplate	2
3	62-3468	Attachment Tab Assembly with Hole	2
		Electrical Bracket Plate	
5	102-7355	Breakaway Bracket	1
		1/4"-20 x 1" Hex Head Bolt, Grade 5, ZP	
7	201-0192	#10-32 1/2" Round Slotted Head Screw	2
8	201-0851(after 4/12/23)	1/2"-13 x 3-3/4" Hex Head Bolt, Grade 5, ZP	2
	201-0051(prior to 4/12/23)	1/2"-13 x 1-1/2" Hex Head Bolt, Grade 5, ZP	4
9	202-0047	#10-32 Hex Nut	2
10	202-0094	1/2" Hex Nylon Nut, ZP	2
11	202-0102	1/4"-20 Hex Nylon Nut, ZP	4
12	203-0001	1/4" Flat Washer, ZP	4
13	203-0005	1/2" Flat Washer	4
14	203-0012	1/2" Lock Washer, ZP	2
15	203-0054	#10 Lock Washer, ZP	2
16	226-0049(not shown)	Class IV Safety Cables	2
17	229-0512(not shown)	1/2" Quicklink, ZP	2
18	` ,	Black Cap Plug Receiver	

#### **Important:**


Use only genuine factory replacement parts on your baseplate. Do **NOT** substitute homemade or non-typical parts. If a bolt is lost or in need of replacement, for your safety and the preservation of your baseplate, be sure to use a replacement bolt of the same grade (In most cases it will be Grade 5, please reference the parts list above). Replacement parts may be ordered through your nearest Blue Ox® Dealer or Distributor. Failing to follow and/ or altering these installation instructions in either installation or required equipment will void the manufacturer's warranty. Towing behind a non-motorized vehicle will void the warranty.

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions

#### Bronco (Modular Bumper) Fascia Removal:




1a. Most Models: Remove the four (4) push pins from plastic tow hook cover. Unsnap cover and remove. Set cover aside to be reinstalled later. Do this on both sides of the vehicle.





1b. Raptor Models: Remove the seventeen (17) push pins from plastic bumper cover. Pull on area around tow hooks to unsnap cover and remove. Set cover aside to be reinstalled later.


2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions



 Using a 15MM socket, remove the three (3) bolts from the tow hook. Do this on both sides of the vehicle. Remove tow hooks with bumper and set aside to be reinstalled later. Tow hooks will not be reinstalled.




3. **Raptor Models**: As the bumper is removed, unplug the one (1) electrical connection on the driver side of the vehicle





4. Using a 1/2" drill bit, drill out hole on the out side of the frame. Do this on both sides of the vehicle.



5. Using a 10MM socket, remove the one (1) bolt (white) from the tow hook bracket. Remove tow hook, it will not be reinstalled. Then using a 13MM socket, remove the four (4) bolts (gray) holding the tow hook bracket onto the bumper. Set bracket aside to be reinstalled on the bumper later. Do this on both sides of the vehicle.

continued on page 9

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions

#### Bronco (Standard Bumper w/ D-Rings) Fascia Removal:





1. Unsnap D-ring cover. Unplug the sensor from the back of the cover. Remove and set cover aside to be reinstalled later. Do this on both sides of the vehicle.



Using a 15MM socket, remove the three

 (3) bolts from the D-ring. Do this on both sides of the vehicle. Remove D-rings with bumper. As the bumper is removed disconnect wire loom from driver side of the vehicle (inset). Set the bumper aside to be reinstalled later.




Using an 8MM socket, remove the one

 bolt from the D-ring bracket. Remove

 D-ring, it will not be reinstalled. Do this on both sides of the vehicle.

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions



Using a 13MM socket, remove the four

 bolts holding the D-ring bracket onto
 the bumper. Set bracket aside to be
 reinstalled on the bumper later. Do this on both sides of the vehicle.



5. Using a 1/2" drill bit, drill out hole on the out side of the frame. Do this on both sides of the vehicle.

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions


#### **Baseplate Installation:**



 Using a reciprocating saw, cut and remove the indicated area of the tow hook bracket. Do this on both D-ring brackets. Reinstall brackets onto bumper.



Slide the baseplate into the frame. Do this on both sides of the vehicle.
 Note for Baseplates Made Prior to (4/14/23): There is a notch in the baseplate tube that denotes the side of the vehicle each piece corresponds with. The driver side has a notch at the top while the passenger side has a notch on the bottom of the tube.





3a. **Baseplates Made Prior to (4/14/23)**: Install the two (2) 1/2" bolts with flat washer and lock washer, one (1) on each side of the frame. Do this on both sides of the vehicle.

<sup>\*\*</sup> Use Loctite® Red on all bolt threads and tighten all bolts to the appropriate torque. \*\*

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions





3b. **Baseplates Made After (4/12/23)**: Install the one (1) 1/2" bolt with flat washers, lock washer, and nut. Do this on both sides of the vehicle.

\*\* Use Loctite® Red on all bolt threads and tighten all bolts to the appropriate torque. \*\*





4. **Optional:** Attach the breakaway switch to the breakaway bracket using the provided one (1) 1/4" x 1" bolt with flat washer and nut (left). Then attach breakaway bracket with switch to the bumper on the driver side of the vehicle using the existing bolt and hardware (right).

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions



Using a 15MM socket, remove the four
 (4) bolts from the belly pan. Set belly ban aside to be reinstalled later.



6. Attach the permanent baseplate safety cables to the provided convenience link on the baseplate. The photo above shows the recommended installation of the cables to frame of vehicle. Additional options may interfere with suggested mounting; in this case, secure the cables to a solid piece of the frame as described in the General Information sheet. Be sure the safety cables do not rub against any hoses or moving parts. Do this on **BOTH** sides of the vehicle. Reinstall belly pan.



7. Slide bumper onto vehicle and reattach electrical on driver side. Then install the three (3) existing bolts. Do this on both sides of the vehicle.

\*\* Use Loctite® Red on all bolt threads and tighten all bolts to the appropriate torque. \*\*



8. Hold electrical bracket up to the bumper on the driver side of the baseplate and mark spot. Using a 1/4" drill bit, drill a hole in the bumper. Attach bracket to the bumper using one (1) 1/4" x 1" bolt with flat washer and nylon lock nut.

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions



9a. Reinstall belly pan. Hold tow hook cover as close to its original position, mark and trim the covers as needed. Reinstall the covers.



9b. Reinstall belly pan, D-ring covers and reconnect electrical.



9c. Reinstall belly pan. Hold tow hook cover as close to its original position, mark and trim the covers as needed. Reinstall bumper cover.

2021-2023 Ford Bronco (Modular Bumper) (Includes Raptor, ACC, Shutters, & Turbo) 2022-2023 Ford Bronco (Standard Bumper w/ D-Rings)(Includes ACC, Shutters, & Turbo) Installation Instructions

#### **CUSTOMER SERVICE COMMITMENT**

Blue Ox® is committed to providing you with exceptional customer care throughout your lifetime with our products. Our team is here to assist you with any questions you may have regarding the performance of your product. Simply call (402) 385-3051 and you can speak with our technical service team.

Additionally, please visit our website to see which rallies our team will be attending. For a nominal fee, our service technician will service your towing system to ensure it's in proper working condition. Also, as a commitment to our customers, should you visit our factory, you can stay at our full service Blue Ox® campground at no charge along with enjoying a factory tour.

Again, thank you for being our customer and for the confidence you have shown in the performance of our products. It is because of customers like you we enjoy the success we have today.



© 2022 Blue Ox One Mill Road, Industrial Park Pender, Nebraska 68047 Phone: (402) 385-3051 Fax: (402) 385-3360 www.blueox.com

#### **General Information**

- 1. Ensure that your product(s) are registered online at www.blueox.com. It is crucial to register your product(s) so that you may be alerted of product offerings, updates, upgrades, maintenance and safety bulletins, and/ or recalls.
- 2. It is the owner's responsibility to inspect all towing equipment for cracked welds, missing or worn parts and loose bolts before each towing trip. Be sure to use Loctite® Red on all bolts and tighten to the recommended specifications.
- 3. It is the owner's responsibility to hook up all towing equipment per manufacturer's instructions/recommendations.
- 4. Remove the attachment tabs when not in use (if applicable).

#### **Notice To Baseplate Installer**

- 1. It is YOUR responsibility to watch for:
  - Oil cooler and air conditioner lines
  - Electrical wires and hoses
  - Missing parts or attaching points on the frame
  - \*\* If the baseplate is improperly installed and is against a wire or hose, it could cause fluid leaks or electrical shorts some time after the actual baseplate installation.

#### **Permanent Baseplate Safety Cable Installation**

Permanent baseplate safety cables are strongly recommended when towing a vehicle with a tow bar. The principle function of the permanent baseplate safety cables is to prevent the towed vehicle from breaking loose in the event the connection between the frame of the towed vehicle and the baseplate fails or becomes disconnected. The cables must be connected from the baseplate to the frame rail or cross member of the vehicle's frame. The illustrations below show the possible arrangements recommended by Blue Ox®. Each permanent baseplate safety cable must have an adequate weight rating for the towing system. The weight rating of the two (2) cables together will not qualify.

Do not mount the permanent baseplate safety cables against wires, hoses or brake lines.

These permanent baseplate safety cables should remain installed as long as the baseplate is installed on the vehicle. Permanent baseplate safety cables are to be used in conjunction with, and NOT a replacement for legally required safety cables attaching the towed vehicle to the towing vehicle.





### Option #2

(Baseplates with out Convenience Link Tabs)



# BLUE OX ORIGINAL PURCHASERS THREE YEAR LIMITED WARRANTY

Automatic Equipment Manufacturing Company ("Automatic") warrants to the original (first) retail purchaser that this product, manufactured by Automatic, shall be free from defect in material and workmanship under normal use and service for a period of three years from the date of delivery.

During said three-year period, Automatic will repair or replace any parts that have been returned by the original purchaser, to the factory, transportation prepaid, and in Automatic's sole and absolute opinion found to be defective.

Limitations on Warranty Coverage:

Coverage under this warranty will be valid only if the customer warranty card is returned by the original purchaser within 30 days of purchase.

Coverage under this warranty will be effective only when a copy of the original invoice, showing date and place of purchase, accompanies any claim for warranty. This warranty is NON TRANSFERABLE.

This limited warranty will not cover, in any way or form, any alleged damages caused by incorrect or improper installation, improper use, modification or neglect of product, failure to properly service and maintain, misuse, act of God, accident or failure of the user to follow guidelines contained in the instructional material provided by Automatic.

This warranty does not cover normal wear and tear, paint or rust.

Warrantor assumes no responsibility to the owner for loss of use of product, loss of time, inconvenience or any other damage consequential or otherwise. Including, but not limited to mileage, expense of transporting of product, return shipping expense, mechanics travel time, telephone, road service, towing, and rental during repairs, travel, lodging, loss or damage to personal property or loss of earnings.

REPAIR OR REPLACEMENT AS SET FORTH IN THIS LIMITED WARRANTY IS THE SOLE EXCLUSIVE REMEDY OF THE PURCHASER. AUTOMATIC SHALL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR BREACH OF ANY EXPRESS OR IMPLIED WARRANTY ON THIS PRODUCT. EXCEPT TO THE EXTENT PROHIBITED BY APPLICABLE LAW, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED IN LENGTH TO THE DURATION OF THIS WARRANTY.

Please visit <a href="http://blueox.com/warranty/">http://blueox.com/warranty/</a> to register your warranty

